



## ACCURPRESS ACCELL Preventive Maintenance Program

| Machine:   |
|--|
| ☐ Check machine level and anchors – re-level if necessary  |
| ☐ Inspect ram way boxes and preload – re-torque and shim if necessary  |
| ☐ Check all gears, fans, motors, pumps bearings and mechanical connections   |
| ☐ Inspect ram level motor and chain – adjust if necessary  |
| ☐ Grease the main motor fittings   |
| ☐ Check tooling alignment/adjust as necessary  |
| ☐ Perform test bends on both ends of machine to verify ram is leveled  |
| ☐ Inspect all encoders and advise  |
| ☐ Change hydraulic oil and filter (*1)   |
| ☐ Check all electrical connectors on top of machine  |
| Backgauge:   |
| ☐ Clean and re-lube backgauge guide rails and roller bearings  |
| ☐ Inspect gear belt for tension and wear – adjust or replace if necessary  |
| ☐ Align and level backgauge bar  |
| Controls:  |
| ☐ Calibrate electronic tonnage readout   |
| ☐ Inspect all limit switches, wiring , relays & contactors   |
| ☐ Check cooling fans and filters – clean or replace as necessary   |
| ☐ Perform backgauge position test and adjust if necessary  |
| ☐ Clean out main control cabinet   |
| ETS 3000 Customers:  |
| □ Blow out ETS 3000 control head   |
| ☐ Run scandisk / defrag on hard drive  |
| ☐ Save all files/jobs/parameters as a backup   |
| On Request:  |
| ☐ Hydraulic fluid analysis – additional \$100 for testing (*2)   |
|  |
|  |
| *1 Customer must are ander required filter prior to service visit  |
| *1 -Customer must pre-order required filter prior to service visit  Customer must provide required oil onsite at time of scheduled visit |
| Customer must have empty, approved containers available onsite for the transfer of used oil  |
| Customer is responsible for the safe storage and/or disposal of all oils and fluids  |
| *2 – Hydraulic fluid analysis will require pre-order of testing kit  |
|  |